

## FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

## **ELEVATION CERTIFICATE**

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

BUILDING OV			lders, I		100000	- W.	S - 2011
NAME 297		cefie	ld Fores		ADDRESS re Two. Pha	ase One. Rin	bhond Hill,
			ock numbers a			and appropriate the property of	
Bryan C	uttu cou-i-			Lancer Manager and Amaze and	ue Heron	DRIVE	
I certify that the	ne informatio	on on this	certificate rep	resents my be	est efforts to interp	oret the data available	e. I understand that any false
statement may SECTION I E	be punishat	certifi	CATION (Com	ent under 18 opleted by Lo itect, or Surve	U.S. code, Section cal Community Pe eyor)	n 1001. rmit Official or a Regis	stered Professional Engineer
COMMUNITY NO.	PANEL NO.	SUFFIX	DATE OF FIRM	FIRM ZONE	DATE OF CONSTR.	BASE FLOOD ELEV. (In AO Zone, use depth)	BUILDING IS  New/Emergency Pre-FIRM Reg.
130018	3	В	4-17-84	ern or old rail	1987	A	₩ Post-FIRM Reg.
□ □ ord	dinance. The	certifier ift, NGVD	may rely on co	mmunity reconstruct the bu	ords. The lowest fl uilding at this eleva	oor (including basem	community's flood plain ent) will be at an elevation uilding in violation of
	dinance base	ed on elev	ation data and	visual inspec	in compliance wit ction or other reason the community.	th the community's floonable means.	ood plain management
YES NO Th	e mobile hor mmunity's flo	ne locate	d at the address	s described a ordinance, or	above has been tie in compliance wit	d down (anchored) ir h the NFIP Specificat	n compliance with the ions.
MOBILE H	НОМЕ МАКЕ	3 (8) 1999 144 (3) 2 (4) (5)	MODEL	YR.	OF MANUFACTU	RE SERIAL N	NO. DIMENSIONS
(Community F	ermit Officit	al or Regi	stered Professi	onal Enginee	r, Architect, or Su	rveyor)	- 12
NAME Jam	es Whi	tley !	Reynolds		ADDRES 5799	Ogeechee Ro	ad
TITLE La	nd Sur	veyor	CITY	Savana	ah	STATE Geo	orgia <sub>ZIP</sub> 314.
/les	110 1	1111	14/			COUNTY OF THE CITY OF THE COUNTY OF THE COUN	Talk promised broke
SIGNATURE	WE	40	10	Re	DATE 7-21-	aliely value va	925-1362
SECTION II	ELEVATION	CERTIF		rtified by a Lo nitect, or Surv		ermit Official or a Regi	stered Professional Enginee
FIRM ZONE	at a		on of		VD (mean sea leve		st floor (including basement rade at the building site is a
FIRM ZONES	V, V1-V30:	at an ele	that the buildinevation ofelevation of	feet,	erty location descr NGVD (mean sea et, NGVD.	ibed above has the bo level), and the avera	ttom of the lowest floor beam ge grade at the building site
FID. / 30::==				DAM: Loortifu:			
floor elevation	A, A99, AH at	d EMER( feet,	BENCY PROGINGVD. The ele	vation of the h	that the building at nighest adjacent gr	the property location of	described above has the lowe g isfeet, NGVI
floor elevation FIRM ZONE A	ofO: I certify t	hat the bu	NGVD. The ele uilding at the p	roperty locat	nighest adjacent gr ion described abov	the property location of ade next to the building we has the lowest floofeet, NG	g isfeet, NGVI r elevation of
FIRM ZONE A feet, NGVD. T	O: I certify the elevation	hat the bu	NGVD. The ele uilding at the p ghest adjacent	roperty locat grade next to	nighest adjacent gr ion described about the building is	ade next to the buildin	g isfeet, NGVI or elevation of VD.
FIRM ZONE A feet, NGVD. T SECTION III I certify to the walls substant	of	hat the bu of the hig DOFING knowled heable to and effects	NGVD. The ele uilding at the p ghest adjacent  CERTIFICATIO  ge, information the passage o s of buoyancy	roperty locat grade next to DN (Certificat n, and belief, f water and s	nighest adjacent gr ion described above the building is tion by a Registere that the building is structural compone	we has the lowest floo feet, NG  d Professional Engine s designed so that the	g isfeet, NGVI or elevation of  per or Architect)  e building is watertight, wit bility of resisting hydrostati
FIRM ZONE A feet, NGVD. T  SECTION III  I certify to the walls substant and hydrodyn forces associa YES   N	of	peet, hat the bu of the hig  DOFING knowled heable to and effects base floo the event uman inter unless m ors and w	NGVD. The ele uilding at the p ghest adjacent  CERTIFICATIO  ge, information the passage o s of buoyancy d. of flooding, wi ervention mean neasures are ta rindows).	vation of the hard property locat grade next to DN (Certificate), and belief, f water and so that would be a that water we ken prior to the property location of the prior to the property location of the prior to t	nighest adjacent grion described above the building is— tion by a Registered that the building istructural compone e caused by the floodproofing by the flood to prevention of the flood to prevention in the floo	we has the lowest flooffeet, NG  ad Professional Engine s designed so that the ents having the capal lood depths, pressure the achieved with huming when floods up to	g isfeet, NGVI or elevation of eer or Architect) e building is watertight, wit bility of resisting hydrostatis velocities, impact and uplice.
FIRM ZONE A feet, NGVD. To SECTION III  I certify to the walls substant and hydrodyn forces associated and YES In Section III  YES In Section III  YES In Section III	of	peet,  hat the buy of the hig  DOFING  knowled heable to hand effects base floo the event uman inter unless m ors and w  If the build tions is YII	NGVD. The ele uilding at the p ghest adjacent  CERTIFICATIO  ge, information the passage of s of buoyancy d. of flooding, with ervention mean neasures are ta rindows). ding be occupi ES, the floodpr	vation of the hard property locat grade next to DN (Certificate), and belief, f water and so that would be a so that water we want to the day a reside to ofing cannot be a so that wooding cannot be a so that water we have a so a reside to of the solution	nighest adjacent grion described above the building is— tion by a Registered that the building istructural compone caused by the floodproofing by the flood to preventence?	ade next to the buildin  ve has the lowest floo  feet, NG  ad Professional Engine s designed so that the ents having the capa ood depths, pressure be achieved with hum and when floods up to t entry of water (e.g., ating purposes and th	g isfeet, NGVI or elevation of  eer or Architect)  e building is watertight, wit bility of resisting hydrostatis velocities, impact and upli an intervention?  the base flood level ocbolting metal shields over
FIRM ZONE A feet, NGVD. To SECTION III  I certify to the walls substant and hydrodyn forces associated YES IN SECTION III  YES IN SECTION III	of	hat the buyof the high of the eable to base floor the event uman inter unless mors and will the built tions is YU stead. Con	NGVD. The ele uilding at the p ghest adjacent  CERTIFICATIO  ge, information the passage o s of buoyancy d. of flooding, wi ervention mean neasures are ta rindows). ding be occupi ES, the floodpr mplete both the	vation of the hard property locat grade next to DN (Certificate), and belief, f water and so that would be a so that water we want to the day a reside to ofing cannot be a so that wooding cannot be a so that water we have a so a reside to of the solution	nighest adjacent grain described above the building is tion by a Registered that the building istructural componer caused by the floodproofing building the flood to preven the credited for rand floodproofing candidated as a second floodproofing candidated for rand floodproofing candidated floodproofing ca	ade next to the building we has the lowest floor feet, NG and Professional Engine as designed so that the ents having the capalood depths, pressure to eachieved with huming when floods up to a tentry of water (e.g., ating purposes and the ertificates.	g isfeet, NGVI or elevation of vD.  eer or Architect)  ee building is watertight, wit bility of resisting hydrostati is velocities, impact and uplican intervention?  the base flood level ocbolting metal shields over eactual lowest floor must be
FIRM ZONE A feet, NGVD. To section III  I certify to the walls substant and hydrodyn forces associated by YES IN  YES IN  If the answer is completed and FIRM ZONES	of	peet, hat the buse of the high control of the high control of the high control of the event the	NGVD. The ele- uilding at the p ghest adjacent  CERTIFICATIO  ge, information the passage o s of buoyancy d. of flooding, wi ervention mean neasures are ta rindows). ding be occupi ES, the floodpr mplete both the O and AH;	vation of the haroperty locat grade next to DN (Certificate), and belief, f water and state would be a that would be stated water water water to the das a reside coofing cannot be elevation and the control of the coofing cannot be elevation are stated or coofing cannot be elevation are stated or coofing cannot be elevated or coofing cannot be	nighest adjacent grain described above the building is tion by a Registered that the building istructural componer caused by the floodproofing building the flood to preven the credited for rand floodproofing candidated as a second floodproofing candidated for rand floodproofing candidated floodproofing ca	ade next to the building we has the lowest floor feet, NG and Professional Engine as designed so that the ents having the capation depths, pressure the achieved with huming when floods up to the entry of water (e.g., arting purposes and the entificates.	g isfeet, NGVI or elevation of vD.  eer or Architect)  ee building is watertight, wit bility of resisting hydrostati is velocities, impact and uplican intervention?  the base flood level ocbolting metal shields over eactual lowest floor must be
FIRM ZONE A feet, NGVD. To SECTION III  I certify to the walls substant and hydrodyn forces associated YES IN  YES IN  If the answer to completed and FIRM ZONES  THIS CERTIFIE	of	hat the buyof the high of the eable to base floor the event uman inter unless mors and will the built tions is YI stead. Con II-V30, AGFOR IS SI	NGVD. The ele uilding at the p ghest adjacent  CERTIFICATIO  ge, information the passage o s of buoyancy d. of flooding, wi ervention mean neasures are ta rindows). ding be occupi ES, the floodpr mplete both the O and AH;	vation of the haroperty locat grade next to DN (Certificate), and belief, f water and state would be the state water when prior to the das a residuo of local control of the state water when prior to the das a residuo of local control of local c	nighest adjacent grain described above the building is tion by a Registered that the building is structural compone e caused by the flood floodproofing by the flood to preven the credited for rand floodproofing componence?  It be credited for rand floodproofing componence?  Certified F	ade next to the building we has the lowest floor feet, NG and Professional Engine as designed so that the ents having the capations depths, pressure to eachieved with huming when floods up to a tentry of water (e.g., ating purposes and the ertificates.  Floodproofed Elevation (Check One)	g isfeet, NGVI or elevation of vD.  eer or Architect)  ee building is watertight, wit bility of resisting hydrostati is velocities, impact and uplican intervention?  the base flood level ocbolting metal shields over eactual lowest floor must be
FIRM ZONE A feet, NGVD. To section III  I certify to the walls substant and hydrodyn forces associated YES IN  YES IN  If the answer is completed and FIRM ZONES  THIS CERTIFICATION TO SECTIFICATION III  CERTIFIER'S IN  James W.	of	hat the buyof the high of the eable to base floor the event uman inter unless mors and will the built tions is YI stead. Con II-V30, AGFOR IS SI	NGVD. The electric properties of the passage of the	vation of the haroperty locat grade next to DN (Certificaton, and belief, f water and state would be state water when prior to the das a residuo of location and belief as a residuo of location and belief, f water and settle and belief as a residuo of location and belief as a residu	nighest adjacent grion described above the building is— tion by a Registered that the building istructural compone e caused by the floodproofing by the flood to preven the floodproofing componence? It be credited for read floodproofing componence	ade next to the building we has the lowest floor feet, NG and Professional Engine as designed so that the ents having the capations depths, pressure to eachieved with huming when floods up to a tentry of water (e.g., ating purposes and the ertificates.  Floodproofed Elevation (Check One)	g isfeet, NGVI  or elevation of  vD.  eer or Architect)  ee building is watertight, with bility of resisting hydrostatis velocities, impact and uplifular intervention?  the base flood level octolling metal shields over  e actual lowest floor must befeet, (NGVD)  LICENSE NO. (or Affix Seal) 2249  ZIP
FIRM ZONE A feet, NGVD. To section III  I certify to the walls substantiand hydrodyn forces associated YES IN  YES IN  If the answer to completed and FIRM ZONES  THIS CERTIFIER'S James Wall  TITLE  Land Su	of	hat the buyof the high of the eable to base floor the event uman inter unless mors and will the built tions is YI stead. Con II-V30, AGFOR IS SI	NGVD. The electric properties of the passage of the	vation of the haroperty locat grade next to DN (Certificate n., and belief, f water and state would be state water water water bed as a residuo of ling canno be elevation are BOTH SECTION COMPANY Helmly ADDRESS Ogeech	ion described above the building is tion by a Registered that the building istructural componer caused by the floodproofing by the flood to preven the floodproofing componer caused by the flood to preven the floodproofing componer caused by the flood to preven the floodproofing componer caused by the flood to preven the floodproofing componer caused by the floodproofing caused by the floodproofing componer caused by the floodproofing ca	ade next to the building we has the lowest floor feet, NG and Professional Engine as designed so that the ents having the capations depths, pressure to eachieved with huming when floods up to a tentry of water (e.g., ating purposes and the entificates.  Floodproofed Elevation (Check One)	er or Architect)  e building is watertight, with bility of resisting hydrostatics velocities, impact and upliful an intervention?  the base flood level octolling metal shields over  e actual lowest floor must be provided in intervention.  ICENSE NO. (or Affix Seal)  2249  ZIP  31419
FIRM ZONE A feet, NGVD. To section III  I certify to the walls substant and hydrodyn forces associated YES IN  YES IN  If the answer is completed and FIRM ZONES  THIS CERTIFIER'S IN  James W.  TITLE	of	hat the buyof the high of the eable to base floor the event uman inter unless mors and will the built tions is YI stead. Con II-V30, AGFOR IS SI	NGVD. The electric properties of the passage of the	vation of the haroperty locat grade next to DN (Certificate notes and belief, f water and so that would be a so that water when prior to the das a residuo of the company of the lamly ADDRESS Ogeech CIT	ion described above the building is tion by a Registered that the building istructural componer caused by the floodproofing by the flood to preven the floodproofing componer caused by the flood to preven the floodproofing componer caused by the flood to preven the floodproofing componer caused by the flood to preven the floodproofing componer caused by the floodproofing caused by the floodproofing componer caused by the floodproofing ca	ade next to the building we has the lowest floor feet, NG and Professional Engine as designed so that the ents having the capations depths, pressure to eachieved with huming when floods up to a tentry of water (e.g., ating purposes and the ertificates.  Floodproofed Elevation (Check One)	g isfeet, NGV or elevation of vD.  eer or Architect)  eer or Architect)  e building is watertight, with building is watertight, with building is velocities, impact and uplication in tervention?  the base flood level ocholting metal shields over  e actual lowest floor must build in isfeet, (NGVD)  ICENSE NO. (or Affix Seal) 2249  ZIP

INSURANCE AGENTS MAY ORDER THIS FORM